

## DIGIMEDIA Removable Adhesive Fabric

DIGIMEDIA Removable Adhesive Fabric is a tightly woven fabric with a grey back and a smooth satin finish that delivers the most vivid colors on any printer. This 280g, bright white self-adhesive fabric is made of a grey back polyester base with a repositionable clear adhesive that removes cleanly and easily with no residue.

Optimized for latex, solvent, eco-solvent and UV inks, DIGIMEDIA Removable Adhesive Fabric is a versatile medium for all indoor décor applications including murals, walls, floors and graphics for shelving, kitchen cabinets, mailboxes, glass and more. Competitively priced, DIGIMEDIA Removable Adhesive Fabric is an environmentally friendly PVC-free product that gives you more versatility and quality.

### Substrate

Satin finish reduces glare, 100% polyester fabric for vivid printed colors

Finish	Satin		
	<i>Value</i>	<i>Tolerance</i>	<i>Standard</i>
Thickness (µm)	178	± 10%	ASTM D 1593
Weight (g/m <sup>2</sup> )	372	± 10%	ASTM D 1593
Gloss (45°) (%)	6.6		ASTM D 523
Slip Rating	R10		DIN EN 16165:2021

### Adhesive

Removable/repositionable proprietary micro-encapsulated adhesive

	<i>Value</i>	<i>Standard</i>
Peel Adhesion 20 min (N/25mm)	> 10	FINAT FTM1
Peel Adhesion 24 h (N/25mm)	> 15	FINAT FTM1
Shrinkage (mm)	Max 0,5	FINAT FTM14
Application temperature (°C)	>10	
Service temperature (°C)	-40 to 80	

### Liner

70# stay flat liner

	<i>Value</i>	<i>Tolerance</i>	<i>Standard</i>
Thickness (µm)	118	± 10%	ISO 534
Weight (g/m <sup>2</sup> )	125	± 10%	ISO 536

## DIGIMEDIA Removable Adhesive Fabric

### Durability

- Durability: 4 years (unprocessed and when applied under vertical exposure - normal Central European climate)
- Shelf Life: 1 year from ship date when stored in proper conditions
- This material must be stored at a temperature of 20° C ± 5 ° C and 50% ± 5% relative humidity, without major climate deviations.
- The storage area must be dry and clean.
- Keep the material in the original package when not in use, in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.
- The product must be stored vertically, so that its quality is not compromised.

---

### Printing Methods

- Specially developed for solvent, eco-solvent, latex and UV large format printing.
- This product must be protected with the recommended lamination in order to provide the necessary strength.
- For the best possible print quality, please make sure you are using the correct print profiles.
- An excessive quantity of ink in the product will result in changes in its characteristics, in inappropriate drying, lamination detachment and / or poor product performance.
- Inadequate drying can result in curls, wrinkles and adhesion failures, which is reflected in the result of the material's performance. A minimum drying period of 48 hours is recommended before any further processing. Drying should be done with the product unrolled.

---

### Applications

- Application surface: flat.
- Applications: Indoor advertising of short duration.
- Substrate not recommended for floor graphics (areas with car traffic); flexible or low energy substrates; non-flat surfaces; carton walls painted or unpainted; plaster walls; wallpaper; unclean or rough surfaces surfaces with degraded paint.
- Do not expose to combustible vapors or spills.
- Surfaces on which the material will be applied must be carefully cleaned and free of dust, grease or any other contamination that may affect the material adhesion.
- Non-vertical application results in a significant reduction in durability, as well as climate and angles of sun exposure. It is recommended that the film remains at least 24 hours at the temperature of the workplace before it is used.
- There may be other factors not described here that may influence the performance in the use.

---

### Important Remarks

- Digiprint Supplies is not responsible for the ease or speed of removal of the applied material. It is necessary to have into account the appropriate air and substrate temperatures.
- The user must determine the material's compatibility with the intended specific application, before using it.
- The data provided in this information is based on our knowledge and experience. It is intended to be a source of information and is not a guarantee. It can be subject to change without previous notice.
- Digiprint Supplies is not responsible for misuse or improper storage, never being responsible for loss or damage to third parties.