

## DIGIMEDIA 60/40 Removable Perforated Vinyl

DIGIMEDIA 60/40 Removable Perforated Vinyl is a perforated, white gloss, calendared PVC film with a black back. It is intended for exterior mounted two-way window applications like store-front windows and has a 40% open area, perfect for two-way viewing while offering high-quality imaging. This printable, non-adhesive side is compatible with solvent, eco-solvent & UV inks.

### Substrate

White gloss calendared PVC film with a black back

| Finish              | White Gloss   |                  |                 |
|---------------------|---------------|------------------|-----------------|
|                     | <i>Value</i>  | <i>Tolerance</i> | <i>Standard</i> |
| Thickness           | 6.3 mil       | ± 10%            | ASTM D 1593     |
| Tensile strength    | Minimum 5 MPa |                  | DIN EN ISO 527  |
| Elongation at Break | Minimum 50%   |                  | DIN EN ISO 527  |

### Adhesive

Solvent polyacrylate removable adhesive

|                              | <i>Value</i> | <i>Standard</i> |
|------------------------------|--------------|-----------------|
| Peel Adhesion 24 h (N/25mm)  | 4~6 N/25 mm  | FINAT FTM1      |
| Application temperature (°F) | >50          |                 |
| Service temperature (°F)     | -4 to 149    |                 |
| Storage stability            | 70°F         |                 |

### Liner

140 g/m<sup>2</sup> PE coated, non perforated silicone paper

|                       | <i>Value</i>   | <i>Standard</i> |
|-----------------------|--|-----------------|
| Flame Resistance      | UBC 26-6<br>UBC 26-7   | ASTM E84        |
| Seawater Resistance   | Adhered to glass, after 48h/23°C (73° F) no variation.   |                 |
| Dimensional Stability | Adhered to glass with no shrinkage in cross direction.<br>In length there is approximately 1.0mm.                      |                 |
| Outdoor Durability    | 2 year outdoor durability (under vertical outdoor exposure in normal climate)  |                 |
| Shelf Life            | 1 year from Date of Manufacture when stored at 60 to 77°F (15/25°C) and 50% relative humidity in the original package. |                 |

### Important Remarks

- DIGIPRINT SUPPLIES is not responsible for the ease or speed of removal of the applied material. It is necessary to have into account the appropriate air and substrate temperatures.
- The user must determine the material's compatibility with the intended specific application, before using it.
- The data provided in this information is based on our knowledge and experience. It is intended to be a source of information and is not a guarantee. It can be subject to change without previous notice.
- DIGIPRINT SUPPLIES is not responsible for misuse or improper storage, never being responsible for loss or damage to third parties.

4728 S. Tamiami Trail | Sarasota, FL 34231 | T: +1-941-256-7980 | usa@digiprint-supplies.com